



The **ACLNB-Ka family** of LNBs is designed for the most challenging Ka-band **professional & military** satellite communication systems (ground, SOTP, SOTM, maritime, etc.). Latest technology is applied to obtain the best noise figure, phase noise, gain stability and return losses according to **MIL-STD-188-164C**. The ACLNB-Ka family is a **high reliability** solution designed for **harsh environmental conditions**, with every single production unit **fully tested** in an environmental chamber and delivered with a complete factory acceptance test report.

#### RECEIVER SPECIFICATIONS

|                                       |  |
|---------------------------------------|--|
| Input frequency .....                 | 19.2 to 21.2 GHz                             |
| Input Ka-Band VSWR (50 Ω) .....       | < 1.3:1                                      |
| Output frequency .....                | 950 to 2000 MHz (see options)                |
| Output L-band VSWR (50 Ω) .....       | < 2.0:1                                      |
| Spectrum inversion .....              | None   |
| Max. input level without damage ..... | 0 dBm  |
| Gain .....                            | 60 dB min                                    |
| Gain flatness .....                   | ±1.5 dB over whole BW<br>±0.5 dB over 40 MHz |
| Gain stability (24 hours).....        | ±0.25 dB @ const. temp.                      |
| Gain variation over temperature ..... | ±1.5 dB (±2.0 dB option LN2)                 |
| Noise figure @ 25 °C .....            | ≤ 1.6 dB                                     |
| Noise temperature @ 25 °C .....       | ≤ 130 K                                      |
| Image rejection .....                 | > 45 dB                                      |
| Output P1dB .....                     | > +10 dBm                                    |
| In-band spurious .....                | < -60 dBc @ P <sub>OUT</sub> = 0 dBm         |

#### LOCAL OSCILLATOR

|  |                     |  |  |
|--|---------------------|--|--|
| Output phase noise (IESS-308/309 – 5 dB) |                     |  |  |
| 100 Hz .....                             | -65 dBc/Hz          |  |  |
| 1 kHz .....                              | -75 dBc/Hz          |  |  |
| 10 kHz .....                             | -85 dBc/Hz          |  |  |
| 100 kHz .....                            | -95 dBc/Hz          |  |  |
| External reference .....                 | 10 MHz              |  |  |
| External reference level.....            | 0 dBm ± 5 dB        |  |  |
| Internal reference stability .....       | ±1 ppm (option LN3) |  |  |

#### POWER SUPPLY

|  |                       |
|--|-----------------------|
| DC input voltage .....                 | 13-18 V <sub>DC</sub> |
| Consumption @ 12 V <sub>DC</sub> ..... | 320 mA typ            |

#### MECHANICAL SPECIFICATIONS

|                    |  |
|--------------------|--|
| Size (LxWxH) ..... | 120 x 60 x 40 mm<br>4.7 x 2.3 x 1.6 in |
| Weight .....       | 450 g<br>1.0 lbs                       |
| Finish .....       | RAL 9003 (White)                       |

#### ENVIRONMENTAL SPECIFICATIONS

|                             |                  |
|-----------------------------|------------------|
| Storage temperature .....   | -40 °C to +85 °C |
| Operating temperature ..... | -20 °C to +60 °C |
| Relative humidity .....     | up to 100%       |
| Operating altitude .....    | up to 4500 m     |

#### INTERFACES

|                                      |                        |
|--------------------------------------|------------------------|
| RX input (Ka-Band) .....             | WR42 grooved (PBR 220) |
| RX output (L-Band+DC+Ext.Ref.) ..... | Type N(F) 50 Ω         |

#### OPTIONS

| Ka-band input                        | L-band output                        | LO freq.   | Standard freq. option |
|--------------------------------------|--------------------------------------|--|-----------------------|
| 19.2 to 20.2 GHz<br>20.2 to 21.2 GHz | 1000 to 2000 MHz<br>1000 to 2000 MHz | 18.200 GHz @ 13 V <sub>DC</sub><br>19.200 GHz @ 18 V <sub>DC</sub> | ACLNB-Ka-E11-V2-0A    |
| 19.2 to 20.2 GHz<br>20.2 to 21.2 GHz | 950 to 1950 MHz<br>950 to 1950 MHz   | 18.250 GHz @ 13 V <sub>DC</sub><br>19.250 GHz @ 18 V <sub>DC</sub> | ACLNB-Ka-E11-V2-0B    |

|           |   |
|-----------|---|
| LN1 ..... | RX output connector type SMA(F) 50 Ω    |
| LN2 ..... | Operating temperature -40 °C to +60 °C  |
| LN3 ..... | Internal reference ACLNBDI-Ka-E11-V2-0x |

