

MENOS FNG FLY-AWAY LIGHT

ACFLY-Ku-MENOS-V2



MENOS
Certified Product



اتحاد إذاعات الدول العربية
مجلس التعاون الخليجي
Certified Product

Ed.03

05/10/12

The ACFLY-Ku-MENOS-V2 is comprised of an ODU (1.2m Ku- Band light antenna, RF chain with 4W BUC and LNB) and a communications and video case (with integrated modem, compact MPEG4 AVC encoder appliance, VoIP phone, ATA, MENOS Router, and a rugged laptop dedicated to the MMX MENOS scheduler).

The integrated FNG terminal can be used within the MENOS satellite network environment, intended for the user to contribute Fast News Gathering (FNG) content in a fast, reliable and efficient way. It also provides high-speed Internet, VPN and VOIP services independently of the availability of terrestrial links.

The system integrates the MENOS Multimedia Exchange software (MMX), which manages the live FNG quality video signals. The MMX exchanges FNG video content with the MMX of the MENOS HUB, which then distributes it to the appropriate receivers. The ACFLY-Ku-MENOS-V2 is connected to the MENOS HUB via a MF-TDMS broadband subsystem for data, voice communication and FNG video.

The ACFLY-Ku-MENOS-V2 is a compact, light, quick assembly and cost-effective solution. The 1.2 meter flyaway antenna is packaged in robust portable weatherproof cases. The system is designed for Road/Air/Sea transportation, ready to work under wind loading conditions and on a wide temperature range.

APPLICATIONS

- Fast news gathering video contributions
- IP Access Services
- VoIP collaboration channels

SUPPORTED SERVICES

- Sat3Play MF-TDMA IP Broadband Access, providing high-speed IP connection with built in acceleration
- Support for 1 video FNG contribution
- Integrated MMX GUI and MMX SIT software providing booking and management of FNG sessions
- Fully integrated VoIP services
- Integrated Quality of Service (QoS), prioritizing VoIP and video streaming over best effort IP traffic

TECHNICAL SPECIFICATIONS

ODU specifications

ODU content:

- 1.2m Ku Band Fly-Away Antenna
- 4W Ku Band BUC
- Ku Band LNB

Antenna and RF Specifications:

Reflector	1.2 Meter, 6 segments, Carbon Fibre
Polarization	Linear
Transmit Frequency	13.75GHz – 14.5 GHz
Receive Frequency.....	10.7GHz – 12.75 GHz
Antenna Gain.....	RX: 42.3 dBi; TX: 43.5 dBi
Beam width (-3dBm).....	RX: 0.95°; TX: 0.82°
Isolation Tx – Rx	≥85 dB
Cross Polarization Isolation (on axis)	≥35 dB
Cross Polarization Isolation (-1dB)	≥30 dB

Sidelobe performance:

First side lobe.....	-18dB
1°≤θ<8°.....	29-25 log θ
8°≤θ<48°.....	29-25 log θ
48°≤θ<180°.....	-13 dB

EIRP (System with 10W P1dB SSPA)	49.5 dBW
G/T	20.3 dB/°K

LNB Options:

Option	Frequency band	LO frequency
Low	10.7 – 11.8 GHz	9.75 GHz
High	11.7 – 12.75 GHz	10.6 GHz

Mechanical specifications:

Material.....	Carbon Fiber (6 segments)
Mount Geometry	Elevation over Azimuth
Polarization	Rotation of Feed
Azimuth travel	360°
Elevation travel	25° to 80°
Polarization travel	±60° Continuous
Drive Move	Manual (Sat3Play Point & Play assistance) *

*Optional pointing aid including software and GPS receiver

Comms & Video case specifications

Comms & Video case content:

ACFLY-Ku-Comms, comprised of:	D1 Modem MENOS Router ATA Compact AVC encoder appliance VoIP phone Rugged laptop, with integrated MMX MENOS scheduler
-------------------------------------	--

Encoding Specifications:

• Video:

Video Encoding Profile.....	ISO/IEC 144-10-(MPEG 4 Part 10 or AVC) Progressive Base Line Profile L3 Interlaced Main Profile L3 (no B frames or CABAC in Main) CBR/VBR Quarter-Pel Motion Estimation – (4x4 mode) Deblocking Filter
Video Encoding Bit Rates	300 Kbps – 5Mbs

• Audio:

Audio Encoding Profiles	AAC-Low Complexity
Audio Sampling	32, 44.4 and 48 kHz
Audio Bitrates.....	8-384 AAC-LC

- Transport:
 - Multiplexing Formats.....ISO/IEC 13818-1 MPEG 2 Transport Stream
 - Streaming Format.....ETSI TS 102034
 - Ethernet Protocols.....Telnet, FTP, UDP, RTP/UDP, SDP and SAP support

Laptop Specifications:

Processor	Latitude E6400 ATG - Intel® Core™ 2 Duo P8700 (2.53GHz, 1066MHz, 3MB/25W))
Wireless connectivity	Intel WiFi Link 5100 (802.11 a/g/n 1X2) 1/2 MiniCard with Centrino label
Hard disk	128GB Mobility Solid State Drive
Ram	2GB 800MHz DDR2 memory (2 x 1GB)
Camera	Integrated
Optical Unit	8 x DVD+ /RW Drive
Battery.....	6 Cell 54Whr LI-ION Primary Battery
Temperature	-30°C* to 40°C Operating
Environmental	MIL-STD Dust, vibration (Cat 20,24), altitude, and humidity

Terminal Interfaces:

- 1 digital SDI input (digital video + embedded audio)
- 1 analog CVBS input (PAL/NTSC)
- 2 XLR female audio inputs
- 2 FXS ports for hooking up 2 analogue telephones
- 1 RJ45 Ethernet interface (10/100 Mbps)

▼ POWER SUPPLY

AC input voltage	110/220 VAC (47-63 Hz) (DC as option)
------------------------	---------------------------------------

▼ PACKING*

Case 1 and 2 (weight, dimensions, content).....	2 Cases; Weight < 23 kg (each); LHW < 157cm (each) (Antenna, Feed, BUC, LNB, cables and phone)
Case 3 (weight, dimensions, content)	1 Case; Weight < 19 kg; LHW < 157 cm (ACFLY-Ku-Comms and Laptop)

* Packing can be modified if required

▼ ENVIRONMENTAL SPECIFICATIONS

Operational Winds	32 Km/h
Survival Winds.....	75 Km/h
Ambient Temperature	0°C to +50°C
Non-condensing storage	-40°C to +70°C up to 95% condensing

▼ OPTIONAL

- The system can be enhanced with electronic compass, GPS receiver and inclinometer, together with an aided pointing GUI for assistance during antenna pointing operation
- WiFi adaptor
- Additional SW (video edition, etc) can be integrated upon user request.