

# TEST LOOP TRANSLATOR Ka-BAND HUBMOUNT

ACTLT-Ka-E6-V1



Ed.00  
16/08/16

ACORDE Ka-band frequency test loop translator hubmount (outdoor applications) is integrated in sealed box along with the rest of the necessary elements to convert from transmission Ka-band to reception Ka-band, such as the control card and the power supply.

Specifications have been optimised to provide the user an efficient frequency conversion. It also enables the configuration of the gain level of the converter.

## FEATURES

- Automatic 10 MHz internal/external reference selection
- Remote Control via Ethernet TCP/IP or via serial interface (RS485)
- Low intermodulation distortion
- External alarm via remote control interface
- Compact hubmount package (outdoor applications)

## TECHNICAL SPECIFICATIONS

Input frequency .....	30.0 – 31.0 GHz
Input returns loss .....	15 dB min
Input impedance.....	50 Ω
Output frequency.....	20.2 – 21.2 GHz
Output return loss.....	15 dB min
Output impedance .....	50 Ω
Spurious signal independent.....	< -60 dBm
Attenuation.....	25 to 55 dB
Attenuation adjustment range .....	30 dB
Attenuation adjustment step.....	0.25 dB
Attenuation flatness .....	± 1.5 dB max
Attenuation stability versus temperature .....	± 1.5 dB over the whole range
Noise figure .....	< 20 dB @ max. gain setting
Image rejection.....	> 60 dB
Mute rejection.....	> 50 dB

## LOCAL OSCILLATOR

LO frequency.....	9.800 GHz
Output phase noise:	
100 Hz.....	-65 dBc/Hz
1 kHz.....	-75 dBc/Hz
10 kHz.....	-85 dBc/Hz
100 kHz.....	-95 dBm/Hz
Reference frequency.....	10 MHz
Reference mode .....	Internal (external selected automatically on presence)
Reference input level.....	0 dBm ± 3 dB
Reference stability .....	±5x10 <sup>-9</sup> /day
	±1x10 <sup>-9</sup> /year

## POWER SUPPLY

AC input voltage .....	85 - 265 VAC (47-63 Hz)
Power consumption .....	30 W (typ.)

## ENVIRONMENTAL SPECIFICATIONS

Storage temperature .....	-40 to +80°C
Operating temperature .....	-20 to +60°C
Relative humidity .....	up to 95%
Operating altitude .....	up to 3500 m

## MECHANICAL SPECIFICATIONS

Interfaces:	
RF input .....	2.92 mm female
RF output.....	3.5 mm female
LO monitor .....	SMA female
Ref. ext. input.....	BNC female
AC line .....	MS3112E12-3P
Serial port (RS485) .....	MS3112E12-14S
Ethernet.....	RJF21G (RJ-45)
Dimensions .....	210 x 210 x 65 mm
Weight .....	4 kg
Finish.....	White RAL 9003

## PHYSICAL ASPECT

