



The **ACLNB-Ka family** of LNBs is designed for the most challenging Ka-band **professional & military** satellite communication systems (ground, SOTP, SOTM, maritime, etc.). Latest technology is applied to obtain the best noise figure, phase noise, gain stability and return losses according to **MIL-STD-188-164C**. The ACLNB-Ka family is a **high reliability** solution designed for **harsh environmental conditions**, with every single production unit **fully tested** in an environmental chamber and delivered with a complete factory acceptance test report.

RECEIVER SPECIFICATIONS

Input frequency	19.2 to 21.2 GHz	
Input Ka-Band VSWR (50 Ω)	< 1.5:1	
Output frequency	950 to 2000 MHz (see options)	
Output L-band VSWR (50 Ω)	< 1.3:1	
Spectrum inversion	None	
Max. input level without damage	0 dBm	
Gain	50 dB min / 55 dB max	
Gain flatness	±2.0 dB over whole BW ±0.5 dB over 40 MHz	
Gain stability (24 hours).....	±0.25 dB @ const. temp.	
Gain variation over temperature	±1.5 dB	
	@ 25 °C	@ 50 °C
Noise figure	≤ 1.6 dB	≤ 1.9 dB
Noise temperature	≤ 130 K	≤ 160 K
Image rejection	> 45 dB	
Output P1dB	> +10 dBm	
In-band spurious	< -60 dBc @ P _{OUT} = 0 dBm	

LOCAL OSCILLATOR

Output phase noise	Max.	Typ.
10 Hz	-50 dBc/Hz	-55 dBc/Hz
100 Hz	-70 dBc/Hz	-75 dBc/Hz
1 kHz	-85 dBc/Hz	-90 dBc/Hz
10 kHz	-95 dBc/Hz	-100 dBc/Hz
100 kHz	-100 dBc/Hz	-105 dBc/Hz
1 MHz	-120 dBc/Hz	-125 dBc/Hz
External reference	10 MHz (Auto external on presence)	
External reference level.....	0 dBm ± 5 dB	
Internal reference stability	±2 ppb/day	

POWER SUPPLY

DC input voltage	15-24 V _{DC}
Consumption	10 W typ steady state 12 W typ warm-up

MECHANICAL SPECIFICATIONS

Size (LxWxH)	150 x 100 x 40 mm 5.9 x 3.9 x 1.6 in
Weight	850 g 1.9 lbs
Finish	RAL 9003 (White)

ENVIRONMENTAL SPECIFICATIONS

Storage temperature	-40 °C to +85 °C
Operating temperature	-30 °C to +60 °C
Relative humidity	up to 100%
Operating altitude	up to 4500 m

INTERFACES

RX input (Ka-Band)	WR42 grooved (PBR 220)
RX outputs (L-Band)	Type N(F) 50 Ω
External reference	Type SMA(F) 50 Ω
Power supply	62IN12E8-4S-4-622

All mating connectors provided

OPTIONS

Ka-band input	L-band output	LO freq.	Standard freq. option
19.2 to 20.2 GHz 20.2 to 21.2 GHz	1000 to 2000 MHz 1000 to 2000 MHz	18.200 GHz @ Path 1 19.200 GHz @ Path 2	ACLNBDI-Ka-E11-V3-0A
19.2 to 20.2 GHz 20.2 to 21.2 GHz	950 to 1950 MHz 950 to 1950 MHz	18.250 GHz @ Path 1 19.250 GHz @ Path 2	ACLNBDI-Ka-E11-V3-0B